

**Engineering Data Sheet 400° F**

**Applications:**

The **Zflex** Viton / Glass expansion joints are used in applications where the operating temperature does not exceed 400°F and where a tough, high strength expansion joint is required. Typical applications include wet & dry scrubbers, precipitator inlet & outlet, air heater outlet, induced draft fan inlet & outlets and other associated duct work.

The **Zflex III** Viton / Glass expansion joints can be provided in a flat belt or integral flange geometry.

**Design Temperature / Pressure**

Temperature:	Max.	Min.
	400°F	- 40°F

Excursions up to 700°F for 1/2 hour.

Pressure:	+ 5 psig	- 5 psig
-----------	----------	----------

**Standard Face to Face**

6"	9"	12"	16"
Duct breach opening			
5 1/2"	8 1/2"	11"	15"

**Standard Movements**

Axial Compression			
1 1/2"	2 3/4"	3 1/2"	5"
Axial Extension			
1/2"	1/2"	1"	1"
Lateral offset, ( Resultant)			
1 1/2"	2 3/4"	3 1/2"	5"



**Standard Weight**

Weight per lineal foot (without backup bars)

6" F/F	2.0 lb./ LF
9" F/F	2.4 lb./ LF
12" F/F	2.8 lb./ LF
16" F/F	3.6 lb./ LF



**Integral Flange Geometry**



**Flat Belt Geometry**

